



100% non slip & anti-skid surface

Patented surface enabling vehicles to cross all types of slippery soils: grass, sand, gravel or mud.




ADVANTAGES



- > Retains dust
- > Grip improvement on soil up to 20%
- > Robust
- > Flexible
- > Anti-erosion
- > Permeable
- > Rot-proof
- > 100% recyclable
- > UV & weather resistant
- > Customizable

Technical specifications

Dimension		Weight	Reference White
Width	Lenght		
1,05m 3.5ft	5m 16ft	42kg 93lb	220496-0500
2,1m 6.9ft	5m 16ft	83kg 185lb	220497-0500
4,2m 13.8ft	5m 16ft	170kg 375lb	220498-0500
4,2m 13.8ft	10m 33ft	340kg 750lb	220498-1000



Mobi-vehicle[™] MM3V25 can support up to 80 tons (depending on the type of soil)

Tensile strength*	> 100 kN/m 10 t/m 680lb/ft
Weight	10 kg/m ² 2lb/sqft
Temperature of use & storage*	-40°C / + 80°C -104°F / +176°F

*Non-contractual technical data which does not constitute any guarantee



Mobility : high grip & lift on the ground



Traffic

- > Cars
- > Trucks
- > Construction equipment



- > **Technical surface** enabling traction to wheeled vehicles



- > **Preservation of soil condition**



Up to 5 years warranty



Company certified ISO 9001 and ISO 14001

Quick installation & low maintenance

QUICK INSTALLATION

Mobi-vehicle™ is easy and quick to install.
Unpack, unroll and anchor the mat on the ground !

Depending on your mats' dimensions, the number of eyelets and anchors will be different:

- Stakes of 500mm included (standard)
- Stakes of 1000mm in option
- Earth anchors in option

EASY MAINTENANCE

Excellent corrosion resistance:

- **Galvanized steel anchors**
- **Aluminum rivets and stainless steel eyelets**

Use a broom, a leaf blower or a high pressure water jet to clean Mobi-vehicle™.



Anchors included

Multiple applications

CONSTRUCTION & BUILDING SITES



What are our complementary products ?

Mobi-mat® Accessibility mat AFX



Mobi-vehicle™ Accessibility mat A2X



Mobi-deck™ Rigid panel



Mobi-fence™ Sand & dust fence



 info@mobi-mat.com