



Lightweight & robust surface - easy to install

Patented surface enabling vehicles to cross all types of slippery soils: grass, sand, gravel or mud.

NEW Made with recycled materials



ADVANTAGES



- > Durable
- > Permeable
- > Rot-proof
- > 100% recyclable
- > UV & weather resistant
- > Customizable
- > Flexible
- > Lightweight
- > Robust
- > Retains sand and dust
- > Highly engineered

Technical specifications

Mobi-vehicle™ A2X can support vehicles up to 40 tons (depending on the type of ground)

Dimension		Roll weight	Roll diameter	Golden sand	White
Width	Length				
1m 3.25ft	5m 16ft	10kg 22lb	40cm 16"	300340-0500	-
	10m 33ft	18kg 40lb	50cm 20"	300341-1000	-
	15m 50ft	26kg 57lb	55cm 22"	300341-1520	-
	20m 65ft	35kg 77lb	60cm 24"	300342-2000	-
	25m 82ft	43kg 95lb	65cm 26"	300342-2500	-
2m 6.5ft	30m 98ft	51kg 112lb	70cm 27"	300343-3040	-
	5m 16ft	19kg 42lb	40cm 16"	300348-0500	-
	10m 33ft	35kg 77lb	50cm 20"	300349-1000	-
	15m 50ft	52kg 115lb	55cm 22"	300349-1520	-
	20m 65ft	68kg 150lb	60cm 24"	300350-2000	-
3m 10ft	25m 82ft	85kg 187lb	65cm 26"	300350-2500	-
	30m 98ft	101kg 223lb	70cm 27"	300351-3040	-
	5m 16ft	27kg 60lb	40cm 16"	300352-0500	-
4,20m 13.8ft	10m 33ft	52kg 115lb	50cm 20"	300353-1000	-
	15m 50ft	77kg 170lb	55cm 22"	300353-1520	-
	25m 82ft	126kg 278lb	65cm 26"	300354-2500	-
4,20m 13.8ft	5m 16ft	38kg 84lb	40cm 16"	-	220468-0500
	10m 33ft	72kg 159lb	60cm 24"	-	220468-1000
	15m 50ft	107kg 236lb	65cm 26"	-	220468-1520

Exact widths in m → 0,99m | 1,53m | 1,98m | 3,06m

Tensile strength*	>100 kN/m 10 t/m 680lb/ft
Weight	<2kg/m² 0.4lb/sqft
Temperature: use & storage*	-40°C /+ 80°C -104°F /+176°F
Combustion classification*	UL94 HB
Fire resistance	B _{FL} -s1 (EN 13501-1)

*Non-contractual data



ISO 9001 & ISO 14001 certification



2 years warranty



Non slip surface tested in accordance with EN 16165 standard



Mobility: maximum ground grip

Pedestrians

- > Safe pathway for pedestrians traffic



Traffic

- > Cars
- > Trucks
- > Construction machines



- > **Technical surface** enabling traction to wheeled vehicles



- > **Preservation of soil condition**

Endless installation & low maintenance

QUICK INSTALLATION

Mobi-vehicle™ is easy and quick to install.

Unpack, unroll and anchor the mat on the ground !

Additional anchoring options :

- **Concrete anchoring kit**
- **Wood anchoring kit**
- **Compact ground anchoring kit**
- **Underwater anchoring kit for soft ground**
- **Underwater anchoring kit for compact ground**

EASY MAINTENANCE

Excellent corrosion resistance:

- **Galvanized steel anchors**
- **Aluminum rivets and stainless steel eyelets**

Use a broom, a leaf blower or a high pressure water jet to clean Mobi-vehicle™.



*All anchors are provided with the mat.
Depending on the dimensions of the mats, the number of eyelets and anchors varies.*

Endless applications

CONSTRUCTION



LANDSCAPING



PARKS & GARDENS



What are our additional products?

Mobi-mat® Accessibility mat AFX



Mobi-roller™ Mat dispenser



Mobi-deck™ Rigid panel



Mobi-fence™ Sand & Dust fence



 info@mobi-mat.com